

Flow Meters

U.S. GALLONS

PART NO.	DESCRIPTION
A101523	1" ALUMINUM FLOW METER - 3 TO 50 GPM, MAX PSI 300
A101524	1" NYLON FLOW METER - 3 TO 50 GPM, MAX PSI 150
A101525	1" 316SS FLOW METER - 3 TO 50 GPM, MAX PSI 800
A101526	1" PVDF FLOW METER - 5 TO 50 GPM, MAX PSI 150

METRIC

PART NO.	DESCRIPTION
A101527	1" ALUMINUM FLOW METER - 10 TO 190 LPM, MAX BAR 20.7
A101528	1" NYLON FLOW METER - 10 TO 190 LPM, MAX BAR 10.3
A101529	1" 316SS FLOW METER - 10 TO 190 LPM, MAX BAR 55.2
A101530	1" PVDF FLOW METER - 19 TO 190 LPM, MAX BAR 10.2

- QUALITY BUILT
- FIELD REPLACEABLE LITHIUM BATTERIES
- ENCAPSULATED ELECTRONICS FOR MOISTURE PROTECTION
- THE TOTALIZERS - 1 CUMULATIVE AND 2 RESETTABLE
- THREE CALIBRATION CURVES WITH UP TO 5 CALIBRATION POINTS
- RATE OF FLOW WITH BYPASS
- ONE YEAR FACTORY WARRANTY
- MODELS ALSO COME WITH A 1" CLOSE NIPPLE

Nozzles


PART NO.	DESCRIPTION
A101497	1" POLYPROPYLENE DISPENSING NOZZLE <ul style="list-style-type: none"> • FLOW RATE TO 27 GPM • MAX 75 PSI • STAINLESS HANDLE, SPRING AND PIN • PTFE BUSHING BARB AND SS CLAMP <ul style="list-style-type: none"> • VITON RUBBER PARTS • QUICK RELEASE ACTION • INCLUDES POLYPRO HOSE <p>THIS PRODUCT HAS A WIDE RANGE OF INDUSTRIAL AND AGRICULTURAL APPLICATIONS. IT IS IDEAL FOR FILLING CONTAINERS WITH MILD CORROSIVE FLUIDS.</p>
A101522	1" SINGLE UNION POLY VALVE WITH ANGLE HOSE END <ul style="list-style-type: none"> • FLOW RATE TO 40 GPM • INCLUDES POLYPRO HOSE BARB AND SS CLAMP <ul style="list-style-type: none"> • NO FLUID CONTACT WITH METAL PARTS <p>THIS VALVE IS IDEAL FOR MORE PRECISE METERED FILLING OPERATIONS. USE WITH CORROSIVE MATERIALS.</p>
J101929	1" ALUMINUM DISPENSING NOZZLE <ul style="list-style-type: none"> • FLOW RATE 17 GPM AT 34 PSI • USE FOR DISPENSING FLAMMABLES <ul style="list-style-type: none"> • QUICK RELEASE ACTION <p>USE THIS VALVE WHEN DISPENSING FLAMMABLE LIQUIDS. WHEN THE NOZZLE IS PART OF A PROPERLY GROUNDED PUMP SYSTEM, FLAMMABLE LIQUIDS ARE SAFER TO HANDLE. USE THE STATIC PROTECTION KIT (SHOWN IN THIS CATALOG SHEET) WITH THIS PRODUCT.</p>

Inlet Strainer

PART NO.	PUMP MODELS	CONSTRUCTION
A100109	TT, TB** (1-5/8" O.D.)	PVC/POLYPROPYLENE
A100111	PF, BT (2" O.D.)	316SS
A100337	TT, TB (1-1/2" O.D.)	316SS
A100855	PF (2" O.D.)	POLYPROPYLENE

**FOR USE WITH CPVC TUBE



Discharge Tubing

PART NO.	PUMP MODELS	CONSTRUCTION
J103470	EP	3/4" PVC
J102785	TB, TT	1" PVC
M100076	BT, HVDP	1-1/2" PVC
J100302	PF	1" REINFORCED PVC



Static Protection Kit

PART NO.	PUMP MODELS
A100835	PFS, TBS, TTS, STTS
A101521*	PFS, TBS, TTS, STTS
A100836	BTS, HVDP
A100961	TMS (includes ground wire assy. only)

CONTENTS

- 1 - 4' GROUNDED HOSE WITH SPECIAL ENDS
- 1 - 6' MOTOR/TUBE GROUND WIRE WITH CLAMP AND TWO (AIR OR ELEC.) TERMINALS WITH LOCKWASHERS
- 1 - STAINLESS STEEL HOSE CLAMP
- 1 - #8-32 X 1/4 BRASS RD HD SCREW WITH #8 BRASS LOCKWASHER

*GROUNDED HOSE HAS THREADED END TO ATTACH J101929 ALUMINUM NOZZLE

NOTE: SPECIAL HOSE LENGTHS AVAILABLE UPON REQUEST



2" IPS Drum Adapter

PART NO.	PUMP MODELS	CONSTRUCTION
M100088	BT, PF, TM, HVDP	GALVANIZED STEEL
M100089	TT, TB*	GALVANIZED STEEL
M100090	TT, TB*	POLYPROPYLENE
M100091	TT, TB**	POLYPROPYLENE
M100092	TT, TB*	316SS
M100094	BT, PF, TM, HVDP	316SS
M100095	BT, PF, TM, HVDP	POLYPROPYLENE
J100366	EP	POLYPROPYLENE

*FOR USE WITH STAINLESS STEEL TUBE

**FOR USE WITH CPVC TUBE



Wall Mount Bracket



PART NO.	PUMP MODELS
M100015	TB, PF, TT, TM, BT-1, BT-2
M100740	BT-3

Filter Lubricator



FILTER LUBRICATOR ASSEMBLY	
PART NO.	MOTOR MODELS
A100003	M2, M6, M6X, M18,
A100221	M19, M20

15' AIR HOSE	
PART NO.	MOTOR MODELS
A100009	M2, M6, M6X, M18
J100243	M19, M20



FINISH THOMPSON INC.

921 Greengarden Road • Erie, PA 16501-1591 U.S.A.
Ph 814-455-4478 • Fax 814-455-8518
Email fti@finishthompson.com • www.finishthompson.com

Toll Free USA & Canada 1-800-834-9384
Literature ID No. FT95-566 E, Rev 2, 3-6-08

