

T100 Series High Pressure

Maximum Flow Rate: 98 l/min (26 gpm) 89l BPD

Maximum Pressure: 345 bar (5000 psi)



API 674



WANNER
Hydra-Cell[®]
Seal-less Pump Technology



T100 Series high pressure model
with Stainless Steel pump head.

Available
to Meet
API 674

- Seal-less design eliminates leaks, hazards and the expense associated with seals and packing.
- Low NPSH requirements allow for operation with a vacuum condition on the suction. Positive suction pressure is not necessary, and there is no need for a booster or charge pump.
- Patented Diaphragm Positioning Control (DPC) protects the diaphragms against a closed or blocked suction line.
- Can run dry indefinitely without damage, eliminating downtime and repair costs.
(Note: Intentional dry running not permitted in ATEX zones.)
- Unique diaphragm design handles more abrasives with less wear than gear, screw or plunger pumps.
- Hydraulically balanced diaphragms to handle high pressures with low stress.
- Significantly lower energy costs than centrifugal pumps.
- Rugged construction for long life with minimal maintenance.
- Compact design and double-ended shaft provide a variety of installation options.
- Hydra-Cell T100 Series pumps can be configured to meet API 674 Standards - consult factory for details.



T100 Series High Pressure Performance

Capacities

Model	Max. Input rpm	Plunger Dia.		Max. Flow Capacities			Max. Pressure Ratings			
							Discharge		Inlet	
		Inches	mm	gpm	l/min	BPD	psi	bar	psi	bar
T100S	450	1.375	35	26	98	891	5000	345	500	34

Consult factory when operating below 45 rpm.

Maximum Flow at Designated Pressure





T100 Series pumps feature the Hydra-Cell seal-less design, eliminating clean-up costs from leaking seals or packing and protecting operators from dangerous fluids such as those containing hydrogen sulfide.

Due to the Wanner Engineering Continuous Improvement Program, specifications and other data are subject to change.

T100 Series High Pressure Specifications

Flow Capacities					
Model	Pressure bar (psi)	rpm	gpm	l/min	BPD
T100S	345 (5000)	450	26	98	891
Delivery					
	Pressure bar (psi)		gal/rev	litres/rev	
T100S	34 (500)		0.066	0.249	
	172 (2500)		0.063	0.237	
	345 (5000)		0.059	0.222	
rpm					
Maximum:	450				
Minimum:	45 (Consult factory for speeds less than 45 rpm.)				
Maximum Discharge Pressure					
Metallic Heads:	345 bar (5000 psi)				
Maximum Inlet Pressure 34 bar (500 psi)					
Operating Temperature Limits					
Maximum Liquid Temperature:	82.2 °C (180 °F)				
Diaphragm Material Minimum Service Temperature (Ambient & Liquid):					
Aflas	30 °C				
EPDM	-20 °C				
FKM	5 °C				
Buna-N (HBNR)	-5 °C				
Consult factory for temperatures outside of these ranges.					
Maximum Solids Size	800 microns				
Input Shaft	Left or Right Side				
Inlet Ports	2 inch Class 300 FF ANSI Flange				
Discharge Ports	1-1/4 inch Class 2500 RTJ ANSI Flange				
Plunger Stroke Length	88.9 mm (3-1/2 inch)				
Shaft Diameter	76.2 mm (3 inch)				
Shaft Rotation	Uni-directional (See rotation arrow.)				
Oil Capacity	19.4 litres (20.5 US quarts)				
See page 5 for oil selection and specification.					
Weight					
Metallic Heads:	499 kg (1100 lbs.)				
Fluid End Materials					
Diaphragm Follower Screw:	316 Stainless Steel				
Outlet Valve Retainer:	316 Stainless Steel				
Plug-Outlet Valve Port:	316 Stainless Steel				
Inlet Valve Retainer:	316 Stainless Steel				
See page 5 for customer-specified fluid end materials choices.					
Power End Materials					
Crankshaft:	Forged Q&T Alloy Steel				
Connecting Rods:	Ductile Iron				
Crossheads:	12L14 Steel				
Crankcase:	Ductile Iron				
Bearings:	Spherical Roller/Bronze Journal (outer mains)				
	Steel Backed Babbitt (crankpin)				
	Bronze (wristpin, center mains)				



Calculating Required Horsepower (kW)*

$$\frac{\text{gpm} \times \text{psi}}{1,460} = \text{electric motor hp}^*$$

$$\frac{\text{lpm} \times \text{bar}}{511} = \text{electric motor kW}^*$$

* hp (kW) is required application power.


Attention!

When sizing motors with variable speed drives (VFD): It is very important to select a motor and a VFD rated for constant torque inverter duty service and that the motor is rated to meet the torque requirements of the pump throughout desired speed range.


T100 Series High Pressure Dimensions

Threaded Version inches (mm)

Front View




Side View




*Contact factory for obstruction distances closer than 12 inches (304.8 mm).

Top View



Bottom View



Note: Dimensions are for reference only. Contact Wanner International for certified drawings.

T100 Series High Pressure How to Order

Ordering Information

1	2	3	4	5	6	7	8	9	10	11	12	13	14
T	1	0	0	S	R								

A complete T100 Series High Pressure Model Number contains 14 digits including 8 customer-specified design and materials options, for example: T100SRDTHFEPAX.

High Pressure

Digit	Order Code	Description
1-4	T100	Pump Configuration Shaft-driven API 674 - Contact Wanner International
5	S	Performance Max. 98 l/min (26 gpm) 891 BPD @ 345 bar (5000 psi)
6	R	Pump Head Version ANSI Flanged Ports (FF on Inlet / RTJ on Discharge)
7	D S	Pump Head Material Nickel Aluminium Bronze (NAB) 316L Stainless Steel
8	A E G T	Diaphragm & O-ring Material Aflas EPDM (requires EPDM-compatible oil - digit 13 code D) FKM Buna-N (HBNR)
9	D H N T	Valve Seat Material Tungsten Carbide* 17-4 Stainless Steel Nitronic 50 Hastelloy C
10	D F N T	Valve Material Tungsten Carbide* 17-4 Stainless Steel Nitronic 50 Hastelloy C
11	E T	Valve Springs Elgiloy Hastelloy C
12	M P S T	Valve Spring Retainers PVDF Polypropylene 316 SST Hastelloy C


*Tungsten Carbide valve seat and disc are a matched set and must be purchased together.

Digit	Order Code	Description
13		Hydra-Oil
	A	10W30 standard-duty oil
	B	40-wt. oil
	D	EPDM-compatible oil
	E	Food-contact oil
	H	15W50 high-temp severe-duty synthetic oil
14		Oil Level Monitor Cover
	C	Float switch, normally closed (recommended)
	O	Float switch, normally open
	W	Level transmitter, ATEX, analog output**
	X	Float switch, ATEX, normally closed***


**ATEX instrument only, pump as standard.

***ATEX-compliant pump and float switch.

Note: The Oil Level Monitor Cover is an assembly that replaces the previous back cover on T100 Series pumps. It contains a float switch assembly that can trigger an alarm or shutdown when pre-defined levels of high or low oil are reached. It may also be ordered without a float switch cover.



T100 Series High Pressure



WANNER

Hydra-Cell®

Partners in over 70 Countries

Standards Compliance



Wanner International Ltd.™

WANNER INTERNATIONAL UNITED KINGDOM

8 & 9 Fleet Business Park
Sandy Lane • Church Crookham
Hampshire UK GU52 8BF
t +44(0) 1252 816847
e: sales@wannerint.com

Wanner Engineering, Inc.™

WANNER ENGINEERING WORLD HEADQUARTERS & MANUFACTURING Minneapolis USA

t +1 612-332-5681
e: sales@wannereng.com

REGIONAL OFFICE Texas USA

t +1 940-322-7111
e: sales@wannereng.com

LATIN AMERICAN OFFICE São Paulo, Brazil

t +55 (11) 99582-1969
e: sales@wannereng.com

Wanner Pumps Ltd.™

WANNER PUMPS Kowloon HONG KONG

t +852 3428 6634
e: sales@wannerpumps.com

Shanghai CHINA

t +86-21-6876 3700
e: sales@wannerpumps.com

OFFICIAL UK DISTRIBUTOR:
Michael Smith Engineers Limited
www.michael-smith-engineers.co.uk
freephone: 0800 316 7891

www.hydra-cell.co.uk