



1124A SERIES™, 1324A SERIES™

CAST IRON CONSTRUCTION | UNIVERSAL PRODUCT LINE




ABOUT O-PRO®

Viking Pump® is the leader in internal gear innovation and the latest development is the O-Pro® seal technology. This new series benefits from the enhancement of our own factory engineered and installed seal. This technology features a robust seal and lubrication chamber, all in one.

FEATURES & BENEFITS

- Rugged design provides superior performance in many markets
- Tight clearances offer high efficiency and excellent priming capabilities
- O-Pro® Barrier combines reliable sealing with easy maintenance
- O-Pro® Barrier is standard with FKM elastomers



KK1124A

Shown with O-Pro® Barrier Seal

** RS size is standard with jacketed head, no valve.



CAPACITY
to 1,500 GPM
(340 m³/h)



PRESSURE
to 200 PSI
(14 BAR)



VISCOSITY
100 to 2,000,000 SSU
(20 to 440,000 cSt)



TEMPERATURE*
0°F to +350°F
(-15°C to +175°C)

* Range may increase with end clearance adjustment

PERFORMANCE

MODELS	SPECIFICATIONS					
Non-Jacketed*	Performance			Standard Ports		
O-Pro™ Barrier Seal	Max Speed, RPM	GPM	m³/h	Size, Inches	Type	Orientation
H1124A	1000	8	1.8	1.5	NPT	Right Angle
HL1124A	1000	18	4	1.5	NPT	Right Angle
K1124A	780	80	18	2	NPT	Right Angle
KK1124A	780	100	23	2	NPT	Right Angle
L1124A	640	135	31	2	NPT	Right Angle
LQ1124A	640	135	31	2.5	Flange	Right Angle
LL1124A	520	140	32	3	Flange	Right Angle
LS1124A	640	200	45	3	Flange	Right Angle
Q1124A	470	275	62	4	Flange	Right Angle
QS1124A	470	400	91	6	Flange	Opposite
N1324A	330	535	122	6	Flange	Opposite
R1324A	260	1,000	227	8	Flange	Opposite
RS1324A	260	1,500	340	10	Flange	Opposite

*1324A Series™ includes jacketed parts as standard.

PORTING

- Right Angle (90°) (Rotatable Casing), H-Q
- Opposite (180°), QS-RS
- NPT
- Flanged (ANSI)

SEALING

- O-Pro® Barrier Seal

MOUNTING

- Foot Mount



OPTIONS

- Jacketing (1224A Series™)
- Stainless Steel (1127A Series™ and 1327A Series™)

TYPICAL APPLICATIONS

- Adhesives
- Resins
- Refined Fuels
- Starch
- Chocolate
- Edible Oils
- Polymers
- Liquid Sugars

CURVES



Note: O-Pro® Barrier Seal is patented.

VIKING PUMP®

VIKING PUMP, INC.
A Unit of IDEX Corporation
406 State Street
Cedar Falls, Iowa 50613 U.S.A.
vikingpump.com

CONTACT YOUR STOCKING DISTRIBUTOR TODAY



Michael Smith Engineers Limited
Web: www.michael-smith-engineers.co.uk
Email: info@michael-smith-engineers.co.uk
Freephone: 0800 316 7891