UNIVERSAL PRODUCT LINE

SERIES: 1127A, 1327A

STAINLESS STEEL CONSTRUCTION


ABOUT O-PRO™

Viking Pump® is the leader in internal gear innovation and the latest development is the O-Pro™ seal technology. This new series benefits from the enhancement of our own factory engineered and installed seal. This technology features a robust seal and lubrication chamber, all in one.



FEATURES & BENEFITS

- · 316 stainless steel construction for process fluid compatibility
- O-Pro[™] Guard provides a robust sealing solution for many markets
- O-Pro[™] Guard rebuildable design offers minimal downtime and low cost



VIKING PUMP°

** RS size is standard with jacketed head, no valve.





to 200 PSI (14 BAR)



TEMPERATURE* 0°F to +225°F (-15°C to +105°C)



VISCOSITY* 28 to 7,500 SSU (0.1 to 1,700 cSt)

* Range may increase with end clearance adjustment







PERFORMANCE

MODELS	SPECIFICATIONS					
Non-Jacketed*	Performance			Standard Ports		
O-Pro™ Guard Seal	Max Speed, RPM	GPM	m³/h	Size, Inches	Туре	Orientation
H1127A	760	6	1.4	1.5	Flange	Right Angle
HL1127A	760	13	3	1.5	Flange	Right Angle
K1127A	520	50	11	2	Flange	Right Angle
KK1127A	520	65	15	2	Flange	Right Angle
LQ1127A	520	100	23	2.5	Flange	Right Angle
LL1127A	520	135	31	3	Flange	Right Angle
LS1127A	520	160	36	3	Flange	Right Angle
Q1127A	350	200	45	4	Flange	Right Angle
QS1127A	350	320	73	6	Flange	Opposite
N1327A	280	475	108	6	Flange	Opposite
R1327A	225	880	200	8	Flange	Opposite
RS1327A	225	1280	290	10	Flange	Opposite

^{*1327}A Series™ include jacketed parts as standard.

PORTING

- Right Angle (90°) (Rotatable Casing), H-Q
- Opposite (180°) (Rotatable Casing), QS-RS
- Flanged (ANSI)

SEALING

O-Pro™ Guard Seal

MOUNTING

Foot Mount


OPTIONS


Jacketing (1227A Series™, 1327A Series™)

TYPICAL APPLICATIONS

- · Soaps, Detergents & Surfactants
- · General Chemicals
- · Peanut Butter
- Paints & Inks
- Edible Oils
- Polymers
- Resins

CURVES





VIKING PUMP°

VIKING PUMP, INC.

A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A. Telephone: (319) 266-1741 vikingpump.com

United States

Cedar Falls, Iowa Phone: (319) 266-1741

Canada vikingpumpcanada.com Windsor, Ontario Phone: (519) 256-5438 Europe & Africa vikingpump.com

China - Shanghai Phone: +86-21-5241-5599 **Singapore** Phone: +65-6684-7305

Asia-Pacific idexfmt-asia.com

India - Mumbai Phone: +91-22-6643-5563

Middle East

Latin America

Australia & New Zealand

IEX

Contact Your Stocking Distributor Today