Flow Meters





Part No.	Description	Applicable Model
	FMTKB Flow Meters - Flow Rate & Flow Tota (GPM, LPM, & CMH Units)	lizer
211013	Polypropylene - 1" Hose barb discharge (Factory Calibrated)	PFM, PFP
211013-1	PVDF - 1" Hose barb discharge (Factory Calibrated)	PFV
211013-2	Polypropylene - 1" Hose barb discharge	SFM, SFP
211013-3	PVDF - 1" Hose barb discharge	SFV, SFVV
211013-4	Polypropylene - 3/4" Hose barb discharge	EFP
211013-5	PVDF - 3/4" Hose barb discharge	EFV
GPI Flo	w Meter - User Adjustable Calibration (minimim flow	5 gpm/19 lpm)
A101529	316SS, Factory Mutual, ATEX II 1 GD (gpm or lpm)	PFS, TBS, TT

Discharge Tubing



Safely transfers fluid from pump to container

Part No.	Discharge Hose Description	Applicable Model
107440	3/4" Reinforced PVC [†] / foot	EF
107445	3/4" EPDM For Diesel Exhaust Fluid (DEF) / foot	EF, PFM, SFM-DEF
111609	3/4" Chemical grade Polyethylene (UHMWPE) / foot	EF, PFM, SFM-DEF
111611	3/4" PE Conductive - Ground wire A100831 Required / foot	EFS
J100302	1" Reinforced PVC [†] / foot	PF, TB, T, SF
J102785	1″ PVC / foot	TB, TT
111612	1" Chemical grade Polyethlene (UHMWPE) / foot	PF, TB, TT, SF
111613	1" PE Conductive - Ground wire A100831 Required / foot	PFS, TTS, SFS
111614	1" FDA Compliant Nitrile/ Buna-N / foot	PFS, TTS, SFS
J100322	1-1/2" PVC ††/ foot	BT, HVDP

[†]Maximum operating temperature: 25°F (-4°C) to 150°F (65°C)

Note: Temperatures are based on pumping water.

Nozzles



Safely dispenses and controls fluid filling into containers.

Part No.	Description	Applicable Model
111030-1	1" Barb, SS hose clamp, wetted parts PP & FKM	PF, SF, TB, TT
111030-7	3/4" Barb, SS hose clamp, wetted parts PP & FKM	EF
111030-4	1" Barb, SS hose clamp, wetted parts PVDF & FKM	PF, SF, TB, TT
111030-10	3/4" Barb, SS hose clamp, wetted parts PVDF & FKM	EF
110374	3/4" & 1" FNPT, wetted parts Aluminum, Brass & PTFE	EFS, PFS, SFS, TBS, TTS
107232	1" Barb, SS hose clamp, wetted parts SS & FKM	PFS, SFS, TBS
107231	3/4" Barb, SS hose clamp, wetted parts SS & FKM	EFS

See drum pump nozzle tech fiver for more details and options.

Static Protection Kit




Increases safety when pumping flammable fluids.

Kit includes synthetic rubber cross-linked polyethylene grounded hose with brass fittings, ground wire, and clamps.

Part No.	Hose Description	Applicable Model
A101521	4 ft. hose with threaded 1" MNPT*	PFS, SFS, TBS, TTS
A100835	4 ft. hose with 1" hose barb*	PFS, SFS, TBS, TTS
A100836	4 ft. hose with 1 1/2" hose barb*	BT, HVDP
107429	4 ft. with threaded 3/4" MNPT*	EFS
A100831	Ground Wire Assembly w/ clamp	ALL

*Maximum temperature: -25°F (-32°C) to 150°F (65°C) Note: Special lengths are available. Contact factory. Note: Temperatures are based on pumping water.

SS Hose Clamp





Part No.	Description	Applicable Model
J101756	3/4" For PVC, RPVC, EPDM hose Only	EF
111872	3/4" For UHMWPE, Conductive, & FDA hose	EF
J101832	1" For PVC, RPVC, & EPDM hose Only	PF, SF, TT, TB
111873	1" For UHMWPE, Conductive, & FDA hose	PF, SF, TT, TB
J100832	1-1/2" - 2 For PVC, RPVC, EPDM hose Only	BT, HVDP

^{††}Maximum operating temperature: -41°F (-41°C) to 140°F (60°C)

DRUM/BARREL PUMPS

Inlet Strainers

Prevents intake of objects or particulates.

Part No.	Construction	Applicable Model
A100855	Polypropylene	PFP, PFM
A100111	304 SS	PFS, BT
A100337	304 SS	TTS,TBS
A100109	PVC/PE	TTC





Drum Adapters





Keeps pump snug in container bung and limits the escape of fumes.

Fits standard 2" bung opening

CF Polypropylene (Conductive)

Stainless Steel

P	١.	1	_
г	v		•

Construction	Applicable Model	Part Number
CF Polypropylene (Conduc-	PF, BT, TM, HVDP	111477
tive) w/ NPS & BSPP / US	EF	111477-1
Buttress	SF, TT	111477-2
CF Polypropylene (Conduc-	PF, BT, TM, HVDP	111477-3
tive) w/ NPS & BSPP / EU	EF	111477-4
BCS 70x6	SF, TT	111477-5
	EF	107426
304SS w/ NPT thread	PF, BT, TM, HVDP	M100094
30435 W/ WITCHICAG	TBS, TTS	M100092
	SF	111374
Galvanized steel w/ NPT	PF, BT, TM	M100088
thread	TBS, TTS	M100089
	EFP	107383
PVC/PTFE sealed w/ Buttress thread (for DEF / AdBlue®)	PFM	107418
thread (for BELL) habiaes)	SFM-DEF	111368
	EFP	107384
PVC/PTFE sealed w/ NPT thread (for DEF / AdBlue®)	PFM	107419
unicad (101 DEI / Nabiace)	SFM-DEF	111369

 ${\it AdBlue} \ @ \ is a registered \ trademark \ of \ the \ VDA \ (German \ Automotive \ Industry \ Association)$

Filter / Lubricator Assembly & Air Hose





Maintains a clean and oiled air motor for longer life and good operation. Air hose sold separately.

Part No.	Item	Applicable Model
A100003	Filter / Lubricator	M6, M6X, M18, M65, S4
A100221	Filter / Lubricator	M19, M20, M66
A100009	Air Hose	M6, M6X, M18, M65, S4

Discharge Spout



Install quick disconnect fittings, flow meters, hard piping or hoses with smaller I.D.

Part No.	Hose Description	Applicable Model
108333	3/4" polypropylene barb fitting	PFM, PFP
108334	3/4" PVDF barb fitting	PFV
108335	1" polypropylene MNPT fitting	PFM, PFP
108336	1" PVDF MNPT fitting	PFV
110194	3/4" polypro MGHT garden hose fitting	PFM, PFP
111367-1	3/4" polypropylene barb fitting	SFM, SFP
111367-2	3/4" PVDF barb fitting	SFV, SFVV
111376-1	1" polypropylene MNPT fitting	SFM, SFP
111376-2	1" PVDF MNPT fitting	SFV, SFVV
111377	3/4" polypro MGHT garden hose fitting	SFM, SFP

Wall Mount Bracket



Stores pump upright on the wall.

Part No.	Applicable Model
M100015	PF, TM
M100740	BT w/ electric motors
108287	EF
111380	SF, TB, TT
110118	HVDP

Hose / Nozzle Hanger

Used to store discharge hose on drum.

Part No.	Item	Construction
107443	Hose / Nozzle Hanger	Painted Steel



Chargers



Charges S6 li-ion motor in two hours.

Part No.	Item	Applicable Model
108144	115V charger w/ USA plug	S6
108145	230V charger w/ Euro plug	S6
108286	12V car charger	S6

